



0.5 – 1.0 HP High Pressure Domestic Pumps



Available at a very economical price, Jalraaj features the very best in pump engineering. From robust construction to class-leading electrical components, Jalraaj reflects the quality and durability that consumers expect from Kirloskar Brothers – one of India's leading manufacturers of pumps.

Product Snapshot:

Range and Technical Specification

Head : 6 to 42 metres

Capacity : 3300 to 504 LPH

Power Rating : 0.37 Kw / 0.5 HP

to 0.75 Kw / 1.02 HP

Voltage Range: 180 to 230 Volts

(single phase)

Construction Materials

 Impeller
 : Brass

 Pump shaft
 : Carbon Steel

 Delivery Casing
 : Cast Iron

 Mounting Casing
 : Cast Iron

Motor Body : Extruded Aluminum

Cover NDE : Aluminum

Mechanical Seal : Carbon Ceramic



Self-priming up to 3 metres:

The pump is capable of priming up to 3 metres (sucks water automatically) without a foot valve, at rated head and discharge, doing away with the inconvenience of filling water to start the pump.



Totally Enclosed Fan-cooled (TEFC) motor:

The pump includes a cooling fan enclosed within the motor to protect it from over-heating and damaging electrical parts.



Class "B" insulation:

All electrical parts are shielded with Class "B" insulation, thereby protecting electrical components and its insulation from damage due to extreme temperatures with the use of super enameled copper winding wire in the motor.



Works with wide input voltage: (180 - 230V)

The pump has the capacity to work with wide input voltage range, thereby enhancing performance while reducing damage to electrical parts.



Thermal Overload Protector:

The pump motor features a Thermal Overload Protector that prevents overloading and shields the motor and associated circuit from the effects of fault current.



Lightweight for easy portability:

Jalraaj is constructed with special alloys to keep it lightweight for easy handling. It's compact size and weight enables you to use the pump easily, anywhere, for various applications.

Applications:



Water supply for domestic use in Bungalows, Apartments, Hotels, Farmhouses etc.



Useful in home water booster systems, lawn sprinklers, overhead tanks and water for gardens.

Performance Chart																
PUMP MODEL	POWER RATING		PIPE SIZE		FULL LOAD	DATED	TOTAL HEAD IN METERS									
	KW	HP	SUC.	DEL.	CURRENT	RATED VOLTAGE	6	10	14	18	22	26	30	34	38	42
					(in amps)	VOLIAGE	DISCHARGE IN LITRES PER HOUR									
JALRAAJ	0.37	0.5	25	25	2.0	220	2120	1820	1550	1260	950	660	360			
JALRAAJ-1	0.75	1.02	25	25	4.0	220	3280	2970	2650	2300	1980	1660	1300	970	612	250
JALRAAJ-2	0.75	1.02	25	25	4.5	230	3300	2700	2380	2120	1870	1620	1400	1116	854	504

Note: Performance applicable in cases of liquid with specific gravity 1 and viscosity as of water.

KIRLOSKAR BROTHERS LIMITED

(CIN – L29113PN1920PLC000670)

Registered Office:

Udyog Bhavan, Tilak Road, Pune 411 002, Tel: +91 20 2444 0770 Fax: +91 20 2444 0156

Regional Sales Offices:

Ahmedabad – (079) 26583739. Chennai – (044) 28157769. Kochi – (0484) 2206651. Nagpur – (0712) 2234275.

Corporate Office:

'YAMUNA', Survey No. 98 (3-7), Baner, Pune 411045 Tel: +91-2027214444. Email: mktg.dis@kbl.co.in.



www.kirloskarpumps.com

Bangalore - (080) 23619914. Dewas - (07272) 227302. Kolkata - (033) 24615065. New Delhi - (011) 41501055. Bhopal – (0755) 4218341. Jaipur – (0141) 2223830. Lucknow – (0522) 2326367. Pune – (020) 24440770.







Bhubaneshwar – (0674) 2536421. Jamshedpur – (0) 9430935888. Mumbai – (022) 25289320. Secunderabad – (040) 6687470.